

New Holland GT-A Garden Tractor Specifications



GT22A

MODEL	GT22A
ENGINE	
Horsepower, hp (kW)	22 (16.4)
Make	Kohler Command
Cooling system	Air
Fuel capacity, gal. (L)	4.0
Oil capacity with filter, qt. (L)	2.0
Full flow oil filter	Standard
Low oil pressure warning light	Standard
Full Pressure Lubrication	Standard
Starter key with safety interlock	Standard
TRANSMISSION	
Type	Hydrostatic
Make	Eaton II
Maximum speed, mph (kph)	
Forward, Range 1	7.4 (11.9)
Reverse, Range 1	3.4 (5.5)
Forward, Range 2	4.4 (7.1)
Reverse, Range 2	2.0 (3.2)
Cruise control	Standard, switch located on right fender
BRAKES	
Service brake	Standard
Park brake lock	Standard
FRONT AXLE	Cast iron
ELECTRICAL	
Charging System	15 amp
Battery, 12 volt	340 cca
Lighting, front	Standard
Lighting, rear	Standard
Warning lights	6
IMPLEMENT CONTROL	
Implement clutch (type)	Electric
Implement lift (hydraulic)	Standard
Automatic implement shutoff in reverse	Standard
Drawbar (rear)	Standard
OPERATOR STATION AND CONTROLS	
Full contour seat	Standard
Steering type	Power
Steering wheel	15 in., tilting
Hourmeter	Standard
Gauges	2
WHEELS AND TIRES	
Front	16 x 7.5-8
Rear, standard	23 x 10.50-12
Rear, optional	23 x 10.50-12 Ag Tread
DIMENSIONS, in. (cm)	
Length, overall	76.5 (194.3)
Width, overall	40 (101.6)
Wheelbase	52 (132.1)
Turning radius (inside rear wheel)	20 (50.8)
Net weight, estimated, lbs. (kg)	900 (408.2)

New Holland GT-A Garden Tractor Specifications

GT22A



OPTIONAL MOWER DECKS

42-inch rear discharge
44-inch side discharge (mulch kit optional)
48-inch side discharge (mulch kit optional)
52-inch side discharge (mulch kit optional)
60-inch side discharge

OPTIONAL ATTACHMENTS AND ACCESSORIES

2-bag vacuum grass catcher, 11 cu. ft.
2-bag vacuum grass catcher, 14 cu. ft.
36-inch rotary tiller
48-inch front blade
42-inch single-stage snow thrower
44-inch two-stage snow thrower
Soft side cab
Front-end loader, 350-lb. lift capacity
36-inch lawn sweeper
36-inch lawn roller, 600 lbs.
Dump cart, 8 cu. ft./400 lb. capacity
Dump cart, 10 cu. ft./1200 lb. capacity

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.