

# New Holland G Series Zero-Turn-Radius Mower Specifications



G4010 G4020 G4030 G4050

MODELS	G4010	G4020	G4030	G4050
<b>ENGINE</b>				
Horsepower, hp (kW)	19 (14.2)	21 (15.7)	23 (17.2)	25 (18.6)
Make	Kohler Courage SV590	Kohler Courage SV610	Kohler Courage SV720	Kohler Courage PRO
No. of cylinders	1	1	2	2
Cooling system	Air			
Fuel capacity, gal. (L)	3 (11.4)			4 (15.1)
Full pressure lubrication	Standard			
Starter key w/safety interlock	Standard			
Air cleaner	Standard			
<b>DRIVE SYSTEM</b>				
Type	Dual hydrostatic: transaxle with integral pump and motor; one at each wheel			Twin hydro-gear ZT2800 hydrostatic transaxle with charge pumps
Max speed, forward, mph (kph)	7.0 (11.3)			
Max speed, reverse, mph (kph)	3.4 (5.5)			5 (8.0)
Implement clutch	Electric			
<b>BRAKES</b>				
Service brake	Hydrostatic dynamic braking			
Parking brake Lock	Automatic engagement with steering levers in neutral			Manual LH lever
<b>ELECTRICAL</b>				
Voltage	12 volts			
Charging system (amps)	15			16
<b>OPERATOR STATION AND CONTROLS</b>				
Steering	Dual padded lever hydrostatic with hydraulic dampening			
Seat type	Contoured, high back, adjustable fore and aft			
Armrests	Optional	Optional	Standard	Standard
Cup holder	Standard			
Storage bin	Standard			
Front casters	Double yoke			
<b>WHEELS AND TIRES</b>				
Front Casters	10 x 4 ribbed	10 x 4 smooth	10 x 4 smooth	10 x 4 smooth
Rear	18 x 7.5-8, 2-ply	18 x 9.5-8, 2-ply	18 x 9.5-8, 2-ply	20 x 10, 4-ply
<b>DIMENSIONS, in. (cm)</b>				
Length, overall				
with grass catcher	90.0 (228.6)			NA
less grass catcher	73.1 (185.7)			
Width, overall				
with deck deflector down	53.8 (136.7)	63.0 (160.0)	63.0 (160.0)	65.0 (165.1)
with deck deflector up	46.0 (116.8)	53.5 (135.9)	53.5 (135.9)	53.0 (134.6)
with grass catcher	52.8 (134.1)	56.8 (144.3)	56.8 (144.3)	NA
Height, overall, to top of seat	37.2 (94.5)	40.2 (102.1)	40.2 (102.1)	42.2 (107.2)
Wheelbase	48.1 (122.2)			46.4 (117.9)
Turning radius, inside rear wheel	Zero turn			
Net weight, estimated, lb. (kg)	500 (226.8)	552 (250.4)	565 (256.3)	649 (294.4)

# New Holland G Series Zero-Turn-Radius Mower Specifications



G4010 G4020 G4030 G4050

MODELS	G4010	G4020	G4030	G4050
<b>MOWER DECKS</b>				
<b>(optional mulching kits available)</b>				
42 in. (107 cm) side discharge	Standard	NA	NA	NA
50 in. (127 cm) side discharge	NA	Standard	Standard	NA
52 in. (132 cm) side discharge	NA	NA	NA	Standard
Spindles	2	3	3	3
Anti-scalp gauge wheels.....	Standard.....			
<b>ATTACHMENTS &amp; ACCESSORIES</b>				
2-bag grass catcher (8 cu. ft./23 m <sup>3</sup> ).....	Optional.....			
Rear engine guard	Optional	Standard	Standard	Standard
Engine top cover .....	Optional.....			
Foot assist height of cut kit	Optional	Optional	Standard	Standard
Smooth-tread front tires	Optional	Standard	Standard	Standard
Sunshade kit .....	NA.....			
Hitch kit .....	Optional.....			
Front light kit.....	NA.....			
<b>WARRANTY</b> .....	3 year limited.....			

Visit our Web site at [www.newholland.com/na](http://www.newholland.com/na). Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.