

New Holland Front-End Loader Specifications



110TL 7308

LOADER MODEL

TRACTOR MODEL

Maximum lift height to pivot pin, in. (mm)
 Clearance with bucket dumped, in. (mm)
 Reach @ maximum lift height, in. (mm)
 Maximum dump angle, degrees
 Maximum rollback angle, degrees
 Dig depth, in. (mm)
 Lift capacity to maximum height at bucket pivot pin, lbs. (kg)
 Breakout force at bucket pivot pin, lbs. (kg)
 Loader weight without bucket, lbs. (kg)
 Cycle times
 Raise time, sec.
 Lower time, sec.
 Dump time, sec.
 Rollback time, sec.

110TL 7308 T1510, T1520, TC30

100.5 (2553)
 84.0 (2134)
 12.8 (324)
 38
 20
 4.0 (102)
 875 (397)
 1602 (727)
 516 (234)

Note: Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

PIN-ON LOADER BUCKETS

	Struck	Heaped
60-in. standard material, cu. yd.	0.32	0.40
60-in. heavy duty material, cu. yd.	0.35	0.43
68-in. heavy duty material, cu. yd.	0.38	0.46

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.